

DRIVER, TRACK AND RESULTS

DRIVER Yuya Sahashi **COUNTRY** **WEATHER** **AIR TEMP** **TRACK TEMP** ☐ DRY ☐ INTERMEDIATE ☐ WET
TRACK **TRACTION** ☐ LOW ☒ MEDIUM ☐ HIGH **COMMENTS**
RACE WC2017 **DATE** **QUALY POS.** 12 **QUALY TIME** **STARTING POS.** **FINAL POS.**

1ST SPUR GEARS 2ND
☐ 61 ☐ 62 ☒ 63 ☐ 56 ☐ 57 ☒ 58

1ST PINION 2ND
☐ 18 ☒ 19 ☐ 20 ☐ 23 ☒ 24 ☐ 25

FRONT SHOCK ABSORBERS REAR
550 cst OIL 700 cst
green SPRINGS red
☐ mm REBOUND ☐ mm
☐ ☒ ☐ ☐ ☐ ☒ ☐ ☐

ANTI-ROLL BARS
 FRONT ANTI-ROLL BAR 2.5 REAR ANTI-ROLL BAR 2.8

FRONT TYRES Controlled Tyre REAR
☐ MAKE ☐
☐ SHORE ☐
☐ DIAMETER ☐
☐ 5-MIN WEAR ☐

POWER PACK
ENGINE
 BRAND o.s.2103 TYPE
 GLOWPLUG rp7 CARBØ mm HEAD CLEARANCE mm
EXHAUST
 PIPE o.s. MANIFOLD
FUEL
 BRAND NITRO

CLUTCH
 CLUTCH BELL ☒ ALU ☐ STEEL CLUTCH SHOE ☐ RED ☒ YELLOW ☐ BLACK
 CLUTCH SPRING ex herd CLUTCH BELL GAP 0.6 mm

FLEX CONFIGURATION
 FR WISHBONES INSERTS ☒ PLASTIC ☐ CARBON RR WISHBONES INSERTS ☐ PLASTIC ☒ CARBON FLEX ☐ YES ☒ NO

AERODYNAMIC CONFIGURATION
 BODY BRAND PF BODY POSITION 14 mm
 BODY TYPE R19
 BUMPER INSERTS ☐ OPEN ☒ CLOSE
 AIR TRIM POSITION 18 mm

FRONT REAR
 AERO DISKS ☐ YES ☒ NO SHOCK POSITION CAMBERLINK SHIMS 3 mm AERO DISKS ☐ YES ☒ NO
 OFFSET mm OFFSET mm
 DOWN STOP 0 mm UPPER ARM INSERT ROLL CENTER INSERT FRONT REAR DOWN STOP 8 mm
 FRONT CAMBER R 2 L 2 REAR CAMBER R 3 L 3
 RIDE HEIGHT 8 mm WITH TYRE Ø mm RIDE HEIGHT 9 mm WITH TYRE Ø mm
 SHOCK BRACKET WIDE ☐ NARROW ☒ SUSPENSION BRACKET NARROW ☐ WIDE ☒
 CASTER 4 mm WHEEL BASE ☐ 0 ☐ 1 ☒ 2
 FRONT TOE 1.5 REAR TOE 2
 ROLL CENTER SHIMS FR 0 mm RR 0 mm
 SHIMS 0 mm INSERT POSITION KINGPIN SHIMS 1 mm ACKERMANN INSERTS FORWARD MID REARWARD
 WHEEL BASE ☐ 0 ☒ 1 ☐ 2 ☐ 3 TRACKROD POSITION
 TRACK WIDTH 252 mm TRACK WIDTH 264 mm
 TOTAL CAR WEIGHT grams WEIGHT POSITION grams 38 grams

REMARKS